

**AGI** 

**AGI** 

***POST POUNDERS***





# RENEGADE & RENEGADE+

TRAILER MODEL



## FEATURES

- Renegade mast raises up to 11' 11" with 660 lbs of hammer pressure
- Renegade+ mast raises up to 13' 8" with 720 lbs of hammer pressure
- Bolt on hammer head with several mounting positions to accommodate different post heights
- Greaseless poly slides are low maintenance and worry-free
- Attached post bin to hold and transport posts with the unit
- Standard, hydraulic post hugger with cast iron cones

## OPTIONS

- Square and T-post huggers available
- The optional pilot auger drills all soil conditions and most rock obstructions
- Electric start engine, comes with high vibration battery, mount and fully assembled

# OUTLAW & OUTLAW+

3PT SIDE MAST



## FEATURES

- Outlaw mast height adjusts from 9' 6" to 11' 11" with 660 lbs of hammer pressure
- Outlaw+ mast adjusts from 9' 8" to 13' 8" with 720 lbs of hammer pressure
- Bolt on hammer head with several mounting positions to accommodate different post heights
- Greaseless poly slides are low maintenance and worry-free
- Low center of gravity and wide stance for added strength and stability

## OPTIONS

- Square and T-post huggers available
- Optional pilot auger drills all soil conditions and most rock obstructions

# SHERIFF

SKID STEER OR 3PT CENTER MAST



## FEATURES


- Non-self-contained hydraulic system
- Adjustable height from 9' 6" to 11' 3" with 660 lbs of hammer pressure
- Center mast configuration improves center of gravity and stability of the unit
- Standard, hydraulic post hugger with cast iron cones

## OPTIONS

- Square and T-post huggers available
- The optional pilot auger drills all soil conditions and most rock obstructions
- Self-contained hydraulic system allows you to use the skid steer hydraulics




Square Post Hugger




T-Post Hugger



Cast Iron Cones



Universal Mount Plate  
\*SHERIFF only



Self-Contained Hydraulic System  
\*SHERIFF only

Models						
	RENEGADE TRAILER MODEL	RENEGADE+ TRAILER MODEL	OUTLAW 3 PT SIDE MAST	OUTLAW+ 3 PT SIDE MAST	SHERIFF SKID STEER CENTER MAST	SHERIFF 3 PT SIDE MAST
WEIGHT	2580 lbs/1170 kg	2930 lbs/1329 kg	2220 lbs/1007 kg	2450 lbs/1111 kg	1500 lbs/680 kg	1410 lbs/640 kg
HAMMER WEIGHT	660 lbs/299 kg	720 lbs/326 kg	660 lbs/300 kg	720 lbs/326 kg	660 lbs/299 kg	660 lbs/299 kg
TRANSPORT HEIGHT	8' 2", 8' 10"/ 249 cm, 269 cm	8' 9", 9' 5"/ 267 cm, 287 cm	8' 2", 8' 10"/ 249 cm, 269 cm	8' 9", 9' 5"/ 267 cm, 287 cm	8' 2"/249 cm	8' 2"/249 cm
TRANSPORT WIDTH	7' 2"/218 cm	7' 2"/218 cm	6' 2"/188 cm	6' 2"/188 cm	36"/91 cm	36"/91 cm
TRANSPORT LENGTH	10' 1"/307 cm	10' 6"/320 cm	5' 4"/163 cm	5' 4"/163 cm	43"/109 cm	43"/109 cm
HAMMER HEIGHT MAX	9' 6" - 11' 3"/ 290 cm - 363 cm	9' 8" - 14' 5"/ 295 cm - 439 cm	9' 6" - 11' 11"/ 290 cm - 363 cm	9' 8" - 13' 8"/ 295 cm - 417 cm	9' 6" - 11' 3"/ 290 cm - 363 cm	9' 6" - 11' 3"/ 290 cm - 363 cm
HAMMER HEIGHT MIN	4' 2"/127 cm	4' 2"/127 cm	4' 2"/127 cm	4' 2"/127 cm	4' 2"/127 cm	4' 2"/127 cm
STROKE	64"/163 cm	64"/163 cm	5' 6"/168 cm	5' 6"/168 cm	5' 4"/163 cm	5' 4"/163 cm
DRIVE OPTIONS	540 RPM PTO or 13 HP Honda	540 RPM PTO or 13 HP Honda	540 RPM PTO	540 RPM PTO	***SKID STEER HYD. †SELFCONTAINED HYD.	***TRACTOR HYD. ††SELFCONTAINED HYD.
MIN HYDRAULIC REQUIREMENT	—	—	—	—	10 gpm @ 1500 psi 38 lpm @ 103 bar	10 gpm @ 1500 psi 38 lpm @ 103 bar
TILT ADJUSTMENT - FRONT/BACK	30° (+/- 15° from vert.)	30° (+/-15° from vert.)	30° (+/-15° from vert.)	30° (+/-15° from vert.)	26° (+/-13° from vert.)	26° (+/-13° from vert.)
TILT ADJUSTMENT - LEFT/RIGHT	50° (±25° from vert.)	50° (±25° from vert.)	50° (±25° from vert.)	50° (±25° from vert.)	40° (±20° from vert.)	40° (±20° from vert.)
TIRES	15"	15"	—	—	—	—

\* 2-Position adjustable mast on side mast pounder models

\*\* 4-Position adjustable bolt on cast head on High & Heavy Hitter pounder, 3-Position adjustable bolt on cast head on High & Heavy Hitter Plus Models

‡ Total weight is 720 lbs without ballast

‡‡ Hammer weight is 320 lbs without ballast. User must add ballast for best performance

#### Skid Steer Post Pounders

Includes inline hydraulic oil filter on return line (self-contained units only)

\*\*\* Requires return line plumbed directly into skid steer/tractor hydraulic oil reservoir.

† Self-contained hydraulics has on board oil reservoir with pump & hydraulic motor driven by skid steer hydraulics.

†† Self-contained hydraulics has on board oil reservoir with PTO pump driven by tractor PTO.

Pilot Auger		
	4"/10 CM	6"/15 CM
LENGTH	54"/137 cm	54"/137 cm
WEIGHT	40 lbs/18 kg	57 lbs/26 kg
CARBIDE TEETH #	5	7
FLIGHTING THICKNESS	3/8"/9.5 mm	3/8"/9.5 mm



AGI is a global leader in supplying farm and commercial customers with the manufacturing, planning, and engineering of full equipment solutions for grain, seed, fertilizer, feed, and food. AGI's expertise enables the storage, blending, mixing, conveying, conditioning, processing, and protection of agricultural products and inputs worldwide.

**Your safety is our highest priority.**

Please read and understand the operator's manual and safety decals before using. Use and maintain products properly, and do not modify. Keep guards in place when operating and follow all product manuals and safety decals. For all AGI products, if guards, safety decals, or manuals are damaged or missing, contact your AGI sales or dealer representative for replacements. Images and information contained in this brochure are presented for general information.

AGI and the rolling hills logo are trademarks of Ag Growth International Inc.