



**Livestock Handling Equipment**

*An "under the hat family" Company*

## **Cattle Care Bull Package Chute -Specifications**

### **Working Dimensions**

#### Headgate (Horizontal)

- Opens parallel to 31-1/2" wide
- Inside Height 68" tall
- Neck Extender maximum inside 16" length

#### Squeeze-V Squeeze (with Hydraulic Side Adjust)

- Top opens from 16" to 37" wide
- Center (bottom of widows) opens from 12-1/2" to 29" wide
- Bottom opens from 9" to 22" wide
- Inside 108-1/2" long
- Inside 70-1/2" height
- Chest Rest Height 18-1/2"

#### Tailgate

- Opens parallel to 31-1/2" wide
- Inside Height 68" tall

### **Overall outside Dimensions**

116" Long

74" Wide (with Headgate and Tailgate closed)

82" Tall (with Remote Power Supply)

92" Tall (with Power Supply mounted on Top)

96" Tall (with Swing Arm)

Optional Swing Arm has a 75" Radius from center of the Chute (measured 36" back from the front of the Headgate)

Optional EZ Lift raises the Chute up 16"

## **Miscellaneous Specifications**

Chute Frame constructed primarily of 2-1/2" x 2-1/2" x 1/4" Square Tube  
Chute Sides constructed primarily of 2" x 2" x 3/16" Square Tube  
Interlocking Animat Floor 23" x 95-3/4" x 3/4" (Weight 52 pounds)  
Prince Stack Valve for Controls  
2-5/16" Coupler weight rating of 12,500 pounds on all Portable Attachments  
6-Bolt Rim with ST225 75R15 Tires on all Portable Attachments

## **Cylinders**

Neck Extender (1)2" x 4" and (1)2-1/4" x 4" Re-phasing  
Headgate (Horizontal) (1)1-1/2" x 14" (1)1-3/4" x 14" Re-phasing  
Center Squeeze (1)2" x 6"  
Tailgate (Horizontal) (1)1-1/2" x 14" (1)1-3/4" x 14" Re-phasing  
Optional-Hydraulic Lower Adjust (4)2" x 6" Steering Cylinder  
Optional-EZ Lift Portable (2)2-1/2" x 16" and (2)2-3/4" x 16" Re-phasing

## **Weight** (does not include the Power Supply)

3000 pounds with Horizontal Headgate and Tailgate, with Hydraulic Lower Adjust, without Swing Arm and without EZ Lift Portable.  
3360 pounds with Horizontal Headgate and Tailgate, with Hydraulic Lower Adjust, with Swing Arm and without EZ Lift Portable.  
4020 pounds with Horizontal Headgate and Tailgate, with Hydraulic Lower Adjust, without Swing Arm and with EZ Lift Portable.  
4320 pounds with Horizontal Headgate and Tailgate, with Hydraulic Lower Adjust, with Swing Arm and with EZ Lift Portable.