

## **Cattle Care Chute Power Supply-Specifications**

### **Cattle Care Chute Power Supply Options**

5 Horsepower Electric 220 Volt Single Phase (Horizontal Headgate)

10 Gallon per minute Vein Pump

5 Gallon Reservoir

Dextron III Oil

(2)30' of ½" Hydraulic Hose with Quick Couplers (when remote only)

50 Amp Breaker required

Minimum of 18KW Generator required

200 pounds when mounted on top of the Chute

240 pounds when remote with (2)30' of Hydraulic Hose

Or

3 Horsepower Electric 220 Volt Single Phase (Pivot Headgate)

7 Gallon per minute Vein Pump

5 Gallon Reservoir

Dextron III Oil

(2)30' of ½" Hydraulic Hose with Quick Couplers (when remote only)

50 Amp Breaker required

Minimum of 12KW Generator required

200 pounds when mounted on top of the Chute

240 pounds when remote with (2)30' of Hydraulic Hose

Or

8 Horsepower Honda Gasoline Motor

10 Gallon per minute Pump

5 Gallon Reservoir

Dextron III Oil

(2)30' of ½" Hydraulic Hose with Quick Couplers

Manual Start

200 pounds with (2)30' of Hydraulic Hose

Or

(2)30' of ½" Hydraulic Hose with Quick Couplers